MOBIUS5iB S20

SLIMLINE FRONT-MOUNTING FULLY-COVERED LOUDSPEAKER

DATASHEET Rev. 1.2 | 11.10.23 | E&OE




Product Description

Building upon 20 years of R&D at the cutting edge of invisible speaker technology, the 'iB' update to the Mobius5iB S200 not only provides significant acoustic upgrades, but introduces an entirely new installation technology for plaster finishes. Development of brand new proprietry high frequency transducers in combination with Amina's Optidrive®, Opti-damping® and Reduced Resonance Exciter® technology results in greater low frequency extension, higher sensitivity and smooth high frequency response well in to the ultrasonic region. The slimline Mobius5iB S200 features an all-new integrated backbox that is acoustically tuned and provides protection to the speaker from any potential contaminants ensuring a trouble free installation and long life. The streamlined installation process automatically aligns the speaker to the correct depth, ultimately resulting in a faster, easier installation.

Example Applications

Invisible audio installations with space limitations or when installing into a curved wall or ceiling. Can be supplied with high-impedance 100/70V transformer for integration into high impedance audio systems.





AMINA

Specifications

Mobius5iB/S200

Nominal impedance	4 Ohms
Power handling (100 hour continuous/peak)	50W/100W
Sensitivity (@ 1m/2.83Vrms)	84dBSPL (with 2mm plaster skim)
Frequency response (-6dB)	90Hz - 30kHz
Useable frequency range (+/-10dB)	65Hz - 32kHz
Dispersion angle	180° x 180° at specified frequency range
Electrical connection	Blue butt-splice crimp terminals (14-16 AWG)
Dimensions	450mm x 200mm x 77mm $(17^{3/4"} \times 7^{7/8"} \times 3^{1/16"})$
Product weight	2.3Kg (2lb 7oz)
Fixing requirements	All fixings provided
In-line protection unit	APUi50C_2, APU-RS8iC, APU-RS16iC, or The Guardian Active Protection
Manufacturer limited warranty	10 years

Amina Technologies Limited